

PUBLIC ADDRESS / AMPLIFIERS / MONO

# MA-125

SINGLE-ZONE PUBLIC ADDRESS AMPLIFIER



- ✓ Excellent features
- ✓ Compact size, for desktop use
- ✓ Racking is possible using bracket model MA-2N

ESPECIALLY RECOMMENDED IN:



All sectors

## DESCRIPTION

PA amplifier equipment with excellent performance and a variety of inputs and outputs. Designed for use in PA installations with 100 V line loudspeakers or mono installations with low impedance loudspeakers. Audio inputs with standard market connections: XLR, jack and RCA. Speaker connectors with screw terminals, secure and easy to connect. High sound quality. Compact size, for desktop or 19" rack use. For PA and background music installations with 100 V or low impedance line loudspeakers. Commercial premises, educational centres, monuments, exhibitions, bars, restaurants, etc.



+ Info:  
<https://fonestar.com/MA-125>

## TECHNICAL CHARACTERISTICS

FEATURES	PA amplifier. Phantom power supply. Priority paging.
POWER	180 W maximum, 120 W RMS
RESPONSE	80-16,000 Hz $\pm 3$ dB
DISTORTION	Harmonic: < 0.5 % at 1 kHz
INPUTS	4 balanced mics/lines, combo (XLR and 6.3 mm jack) 600 Ohm 3 mV and 47,000 Ohm 150 mV RMS, switchable 1 aux, 2 x RCA, 47,000 Ohm 250 mV RMS 1 amp in, RCA 10,000 Ohm 1 V RMS 1 tel. input, screw terminal blocks 600 Ohm 100 mV RMS
OUTPUTS	1 line out, 2 x RCA 47,000 Ohm 1 V RMS 1 pre out, RCA 600 Ohm 1 V RMS 1 monitor, screw terminal blocks 600 Ohm 775 mV RMS and 1 W 8 Ohm (aux input)
CONTROLS	Tone: Bass: $\pm 10$ dB Treble: $\pm 10$ dB Volume: inputs 1 to 4, aux and general volume
PHANTOM	24 V in mics 1 to 4, selectable
PRIORITY	Tel. input and mic. 1 depending on signal level, selectable
IMPEDANCE	4 Ohm and 100, 70 and 25 V lines, screw terminals
POWER SUPPLY	230/115 V AC, 290 W and 24 V DC, 161 W
DIMENSIONS	420 x 89 x 300 mm depth. 2 U 19" rack
WEIGHT	9.4 kg
OPTIONAL	MA-2N: mounts for assembly in 19" rack



+ Info:  
<https://fonestar.com/MA-125>