



Model	902.420
Revc	6,800 Ohm
Fo	68,552 Hz
Sd	83,000 cm ²
Krm	564,271 uOhm
Erm	1,073
Kxm	59,014 mH
Exm	0,538
Vas	5,721 mM ³
Cms	584,776 uM/N
Mmd	8,783 mKg
Mms	9,217 g
BL	7,392 T·M
Qms	3,551
Qes	0,494
Qts	0,434
No	0,361 %
SPLo	87,590 dB

Model	902.423
Revc	7,200 Ohm
Fo	45,544 Hz
Sd	141,000 cm ²
Krm	332,517 uOhm
Erm	1,171
Kxm	51,553 mH
Exm	0,595
Vas	14,156 mM ³
Cms	501,443 uM/N
Mmd	23,391 mKg
Mms	24,353 g
BL	10,003 T·M
Qms	5,005
Qes	0,501
Qts	0,456
No	0,258 %
SPLo	86,133 dB

Model	902.426
Revc	7,200 Ohm
Fo	36,699 Hz
Sd	201,000 cm ²
Krm	657,601 uOhm
Erm	1,117
Kxm	54,197 mH
Exm	0,618
Vas	23,634 mM ³
Cms	411,968 uM/N
Mmd	44,014 mKg
Mms	45,653 g
BL	11,918 T·M
Qms	4,945
Qes	0,534
Qts	0,482
No	0,212 %
SPLo	85,276 dB